



ANSI SY	Dongfeng	Pitch	Roller diameter	plates between inner	Pin diameter	pins connecting	Inner plates depth	Plate thickness	Transverse pitch	抗拉 Ultimate tensile strength	每米 Mass per meter
		mm	d1 max	b1 min	d2 max	Lc max	h2 max	T	pt	KN min	kg/m
80H	S16AH-1	25.40	15.88	15.75	7.94	42.8	24.13	3.96	—	55.60	3.1
100H	S20AH-1	31.75	19.05	18.90	9.54	50.6	30.17	4.75	—	86.84	4.52
120H	S24AH-1	38.10	22.23	25.22	11.11	61.6	36.20	5.56	—	125.10	6.6
140H	S28AH-1	44.45	25.40	25.22	12.71	66.4	42.23	6.35	—	170.27	8.3
160H	S32AH-1	50.80	28.58	31.55	14.29	77.3	48.26	7.14	—	222.40	11.2
180H	S36AH-1	57.15	35.71	35.48	17.46	86.4	54.30	7.92	—	281.57	14.83
200H	S40AH-1	63.50	39.68	37.85	19.85	97.3	60.33	9.52	—	347.41	19.16
80H-2	S16AH-2	25.40	15.88	15.75	7.94	75.4	24.13	3.96	32.59	111.20	6.15
100H-2	S20AH-2	31.75	19.05	18.90	9.54	89.7	30.17	4.75	39.39	173.68	9.03
120H-2	S24AH-2	38.10	22.23	25.22	11.11	110.5	36.20	5.56	48.87	250.20	13.13
140H-2	S28AH-2	44.45	25.40	25.22	12.71	118.6	42.23	6.35	52.2	340.54	16.6
160H-2	S32AH-2	50.80	28.58	31.55	14.29	139.2	48.26	7.14	61.9	444.80	22.3
180H-2	S36AH-2	57.15	35.71	35.48	17.46	155.6	54.30	7.92	69.16	563.14	29.36
200H-2	S40AH-2	63.50	39.68	37.85	19.85	175.6	60.33	9.52	78.31	694.82	38.11
80H-3	S16AH-3	25.40	15.88	15.75	7.94	108.0	24.13	3.96	32.59	166.80	12.96
100H-3	S20AH-3	31.75	19.05	18.90	9.54	128.8	30.17	4.75	39.39	260.52	19.64
120H-3	S24AH-3	38.10	22.23	25.22	11.11	159.4	36.20	5.56	48.87	375.30	24.9
140H-3	S28AH-3	44.45	25.40	25.22	12.71	170.8	42.23	6.35	52.2	510.81	33.5
160H-3	S32AH-3	50.80	28.58	31.55	14.29	201.1	48.26	7.14	61.9	667.20	42.26
180H-3	S36AH-3	57.15	35.71	35.48	17.46	210.6	54.30	7.92	69.16	822.40	51.14
200H-3	S40AH-3	63.50	39.68	37.85	19.85	223.0	60.33	9.52	78.31	994.72	61.2
80H-4	S16AH-4	25.40	15.88	15.75	7.94	140.6	24.13	3.96	32.59	347.36	26.2
100H-4	S20AH-4	31.75	19.05	18.90	9.54	167.9	30.17	4.75	39.39	500.40	33.1
120H-4	S24AH-4	38.10	22.23	25.22	11.11	208.3	36.20	5.56	48.87	681.08	44.5
140H-4	S28AH-4	44.45	25.40	25.22	12.71	223.0	42.23	6.35	52.2	889.60	58.35
160H-4	S32AH-4	50.80	28.58	31.55	14.29	263.0	48.26	7.14	61.9	1100.80	77.1
180H-4	S36AH-4	57.15	35.71	35.48	17.46	295.8	54.30	7.92	69.16	1362.16	98.9
200H-4	S40AH-4	63.50	39.68	37.85	19.85	326.1	60.33	9.52	78.31	1779.20	129.6
80H-6	S16AH-6	25.40	15.88	15.75	7.94	246.1	36.20	5.56	48.87	1021.62	66.7
100H-6	S20AH-6	31.75	19.05	18.90	9.54	307.4	42.23	6.35	52.2	1334.40	89.5
120H-6	S24AH-6	38.10	22.23	25.22	11.11	367.1	48.26	7.14	61.9	1779.20	129.6
140H-6	S28AH-6	44.45	25.40	25.22	12.71	423.0	54.30	7.92	69.16	2310.40	174.4
160H-6	S32AH-6	50.80	28.58	31.55	14.29	486.8	60.33	9.52	78.31	2944.80	232.4
180H-6	S36AH-6	57.15	35.71	35.48	17.46	543.6	66.35	10.35	84.23	3689.20	298.4
200H-6	S40AH-6	63.50	39.68	37.85	19.85	603.4	72.37	11.17	90.25	4543.60	381.6